

Icom Filters:

Item name	IF frequency	Mode	Bandwidth	Shape factor*	Application type
FL-44A†	455kHz	SSB	2.4kHz/-6dB	1.75	Narrow filter
FL-52A†	455kHz	CW	500Hz/-6dB	2.0	Narrow filter
FL-53A†	455kHz	CW	250Hz/-6dB	2.0	Narrow filter
FL-96	455kHz	SSB	2.8kHz/-6dB	1.8	Wide filter
FL-222	455kHz	SSB	1.9kHz/-6dB	1.66	Narrow filter
FL-257	455kHz	SSB	3.3kHz/-6dB	1.9	Wide filter
FL-70	9MHz	SSB	2.8kHz/-6dB	1.8	Wide filter
FL-80	9MHz	SSB	2.4kHz/-6dB	1.5	Narrow filter
FL-100	9MHz	CW	500Hz/-6dB	2.8	Narrow filter
FL-101	9MHz	CW	250Hz/-6dB	3.2	Narrow filter
FL-102	9MHz	AM	6kHz/-6dB	3.33	Wide filter
FL-103	9MHz	SSB	2.8kHz/-6dB	1.8	Wide filter
FL-223	9MHz	SSB	1.9kHz/-6dB	1.9	Narrow filter
FL-232	9MHz	RTTY/CW	350Hz/-6dB	2.9	Narrow filter
FL-272	9MHz	SSB	2.4kHz/-6dB	2.0	Narrow filter

\*-60dB BW/-6dB BW

†Non-"A" is 6 mm taller than "A" version. Specs and pinout identical for both versions.